

90W 5G PoE Injector



Product Highlights

- Support 1*5Gbps PoE out port+1*5Gbps Data in port
- Ethernet Ports support 10M/100M/1G/2.5G/5Gbps self-adaptive
- Comply with IEEE802.3af (15.4W), IEEE802.3at (30W), and IEEE802.3bt (90W)
- Support AC 100-240V power supply
- Operating temperature range of 0~40°C

Hardware Features

Description	Specification
Model	HR200-BTG5-N901+
Interface	1*5Gbps PoE out Port 1*5Gbps Data in Port
Port Standard	IEEE802.3 (Ethernet) IEEE802.3u (Fast Ethernet) IEEE802.3ab (Gigabit Ethernet) IEEE802.3x (Flow Control)
PoE Standard	15.4 W (IEEE 802.3af) 30 W (IEEE 802.3at) 90 W (IEEE 802.3bt)
PoE Port Output Voltage	DC 44-57V
Power Supply	AC 100-240V 50/60Hz DC 52V 1.92A
PoE port	Port PoE power output<90W
Structure Information	Product Dimensions: 166*56.5*39.2mm Packaging Dimensions: 203*160*55mm Product Net Weight: 0.2KG Product Gross Weight: 0.4KG
Packing Information	Carton Dimensions: 580*335*445mm Packing Quantity: 40PCS Packing Weight: 17KG
Package Contents	Injector 1pcs, Manual 1pcs, Certificate of Inspection 1pcs
Certification	CE, FCC, RoHS
Installation	Wall Mounting
Operating Temperature	0~40°C
Storage Temperature	-40~85°C
Operation Humidity	5%~90%, non condensing
Storage Humidity	5%~95%, non condensing
Port Led	Green: Power on Red: PoE on Off: Power off
Surge protection	Port surge: Common mode 6KV, Differential mode 2KV Electrostatic ESD 6KV, Air 8KV Power Supply: Common mode 6KV, Differential mode 2KV

Product Structure Diagram

