


10-Port Gigabit Industrial Managed PoE Switch



Product Highlights

- Support: IEEE802.3 IEEE802.3u, IEEE802.3x, IEEE802.3z / ab, IEEE802.1Q, IEEE802.1p, IEEE802.1d/w
- Support PoE power management and PoE Watch dog based on data flow detection
- Supports IEEE802.3af (15.4W) and IEEE802.3at (30W)
- Support SNMP v1/v2/v3
- Supports IGMP Snooping, static multicast filtering, and MLD Snooping filtering
- Support STP(802.1D),RSTP(802.1w),MSTP(802.1s),ERPS
- Support 802.1x port authentication and AAA authentication to enhance network security
- Supporting WEB, Telnet, CLI, SSH management
- IP40 protection level, high-strength housing, DIN35 rail installation
- Industrial grade 4-level design, operating temperature from 40 to 75 ° C
- Support redundant power supply connection and anti reverse connection

Hardware Features

Description	Specification
Model	HR600-AFGM-82S
Interface	8 *1G PoE ports 2 *1G SFP ports 1 * Console port
Port Standard	IEEE802.3 (Ethernet) IEEE802.3u (Fast Ethernet) IEEE 802.3ab (Gigabit Ethernet) IEEE 802.3z (Gigabit Ethernet Fiber Standard) IEEE802.3x (Flow Control) IEEE 802.1D Spanning Tree Protocol IEEE 802.1w Rapid Spanning Tree Protocol
Bandwidth	20Gbps
Packet Forwarding Rate	14.88Mpps
Packet Buffer	4.1Mbit
MAC Address Table	8K
Jumbo Frame	Support
VLAN	VLAN range 1-4094, maximum active VLAN is 4K
Transmission Method	Store and Forward
PoE Standard	IEEE802.3af (15.4W) IEEE802.3at (30W)
PoE Port Output Voltage	DC 48-55V
PoE Ports	Port 1-8 PoE power output <30W
PoE Power Budget	According to the adapter
Power Supply	DC12~55V DC48~55V (PoE) Power wiring: 4 PIN industrial terminals (redundant V1+V1-, V2+V2-)

Hardware Features

Description	Specification
Mainboard Power Consumption	9.8W
Structure Information	Product Dimensions :165*130*65mm Packaging Dimensions : 242*207*86mm Product Net Weight: 0.8KG Product Gross Weight: 1.1KG (excluding power supply)
Packing Information	Carton Dimensions :445*445*510mm Packing Quantity: 20PCS Packing Weight:23KG
Package Contents	Switch 1pcs, Serial cable 1pcs,manual 1pcs,certificate of qualification 1pcs
Fan Quantity	0
Certification	CE、FCC、RoHS
Installation	Desktop,wall mounting installation, rail installation
Surge Protection	Port Surge: Common mode 6KV, differential mode 2KV Electrostatic ESD: Air 15KV, Contact 8KV
Operating Temperature	-40 ~ 75°C
Storage Temperature	-40~85°C
Operation Humidity	10%~90%, non condensing
Storage Humidity	5%~95%, non condensing
PWR Green LED	On: Powered on Off: Powered off
SYS Green LED	On: The system is running normally Off:The system is not running
1-8 Green LED	Slow Flashing: 10/100/1G Link normal Off: Link blocked Fast Flashing: Data transmitting
1-8 Yellow LED	On: PoE powered on Off: PoE powered off
G9-G10 Green LED	On: 10/100/1G Link normal Off: Link blocked Flashing: Link data transmission
RESET	Long press for 6 seconds to restore factory settings

Software Features

Description	Specification
L2 Function	
IPv4	IPv4 VLAN Interface IPv4 Static Routes ARP
Port	Port Switch configuration Port Description configuration Port Speed configuration Port Duplex configuration Port Flow Control configuration Jumbo Frame EEE Fiber Module(DDM)
Link Aggregation	Supports load balance policy; Base on MAC and IP-MAC Static and Dynamic Group Supports LACP
Storm Control	Boardcast suppression Unknown Multicast Unknown Unicast
Port Mirroring	One to one monitor Many to one monitor Ingress/Egress/Both
Port Security	MAC Address Constraints Action: Trap/Shutdown
Port Isolation	Support
Port Rate-limit	Support
Loopback Detection	Support
VLAN	Access/Trunk/Hybrid VLAN Tunnel (Q-in-Q Tunnel) GVRP VLAN range 1-4094, maximum active VLAN is 4K

Software Features

Description	Specification
MAC Address	Dynamic MAC address
	Static MAC address
Spanning Tree Protocol	STP/RSTP/MSTP
	BPDU Filter
	BPDU Guard
	Edge Port
ERPS	Major and sub ring
	up to 16 rings
Smart Ring	Private Ring
	Major and sub ring
	Up to 16 rings
PTP	Ordinary Clock
	Boundary Clock
	Transparent clock
LLDP	Support
Multicast	IGMP Snooping
	IGMP V1/V2/V3
	Router Port
	Static IGMP group address
	IGMP groups filtering
	Querier
QoS	MLD Snooping
	Traffic classification based, Strict priority and WRR
	Port Priority
	802.1P Priority
	IP DSCP Priority
	Supports up to 8 queues per port
Port Shaping	

Software Features

Description	Specification
PoE	
PoE Configuration	PoE Temperature PoE Type/Level/Power/Voltage/Current query PoE Switch Configuration PoE Watchdog Total PoE power budget control PoE power management PoE port priority Per PoE port power limit
PoE Schedule	Support
PoE Port Timer Reboot	Support
Services	
DHCP	DHCP Server IP Pool Static Binding DHCP Relay
	HTTP
Access Protocol	Telnet SSH Manager ACL
Security	
	RADIUS
AAA	TACACS+ 802.1X Base on port/MAC/local/WEB
DHCP Snooping	Support

Software Features

Description	Specification
IP Source Guard	Support
Dynamic ARP Inspection	Support
ACL	MAC ACL
	Port ACL
	IPv4 ACL
	IPv6 ACL
Diagnostics	
Syslog	Logging Message
	Remote Server
Ping	Support
Traceroute	Support
Cable Diagnostics	Support
Equipment Management	
Manager Access	Console
	HTTP
	Telnet
	SSHv2
	SNMP
Manager IP	Static Address
	DHCP Client
	Supports IPv4 and IPv6 address
	DNS
	SNTP
Time Synchronization	
SNMP	Manual Time
	V1/V2C/V3
	Community
SNMP	V3 User
	Group
	Trap Host

Software Features

Description	Specification
SNMP MIB	RFC 1213 MIB-II
	RFC 1493 Bridge MIB
	RFC 1643 Ethernet MIB
	RFC 2819 RMON MIB (Groups 1, 2, 3 and 9)
	RFC 2863 Interface MIB
	Private MIB
RMON	Statistics
	History Configuration
	Event Configuration
	Alarm Configuration
User Management	Congurable user privilege level from 0 - 15;
Firmware Management	Firmware upgrade
	Double Image; Swap between Active and Alternate firmware image.
Configuration Management	Upload and download
Save	Support
Restart	Support
Factory Defaults	Support
Standard Compliance	
IEEE 802.3x flow control and back pressure	
IEEE 802.3ad port trunk with LACP	
IEEE 802.1D Spanning Tree Protocol	
IEEE 802.1w Rapid Spanning Tree Protocol	
IEEE 802.1s Multiple Spanning Tree Protocol	
IEEE 802.1p Class of Service	
IEEE 802.1Q VLAN tagging	
IEEE 802.1x Port Authentication Network Control	
IEEE 802.1ab LLDP	
IEEE 802.3af Power over Ethernet	
IEEE 802.3at Power over Ethernet Plus	
RFC 768 UDP	
RFC 793 TFTP	
RFC 791 IP	

Software Features

Description	Specification
RFC 792 ICMP	
RFC 2068 HTTP	
RFC 1112 IGMP v1	
RFC 2236 IGMP v2	
RFC 3376 IGMP v3	
RFC 2710 MLD v1	
RFC 3810 MLD v2	
ITU-T G.8032 ERPS Ring	

Product Structure Diagram

