

# 5-Port 100Mbps Ethernet Switch(Plastic Shell)



## Product Highlights

- 5 \*100Mbps RJ45 ports
- Compliant with IEEE802.3 and IEEE802.3u standards
- RJ45 port supports 10/100Mbps adaptive
- Supports automatic port flipping (Auto MDI/MDIX)
- The panel indicator LEDs will monitor the working status and assist in fault analysis
- Flow control method, IEEE802.3x standard for full duplex and Backpressure standard for half duplex

## Hardware Features

Description	Specification
Model	HR-SW0050+
Interface	5 *100Mbps RJ45 ports
Port Standard	IEEE802.3 (Ethernet) IEEE802.3u (Fast Ethernet) IEEE802.3x (Flow Control)
Bandwidth	1Gbps
Packet Forwarding Rate	0.744Mpps
Packet Buffer	768Kbit
MAC Address Table	2K
Transmission Method	Store and Forward
Power Supply	AC 100-240V , 50/60Hz DC 5V 1A
Mainboard Power Consumption	0.8W
Structure Information	Product Dimensions :92*51*21.5mm Packaging Dimensions : 93*82*51mm Product Net Weight: 0.062Kg Product Gross Weight:0.132Kg
Packing Information	Carton Dimensions :435*280*395mm Packing Quantity: 100PCS Packing Weight: 14.2KG
Package Contents	Switch 1pcs, Power adapter 1pcs, manual 1pcs,certificate of qualification 1pcs
Fan Quantity	0
Installation	Desktop
Surge Protection	Port Surge:Common mode 2KV, differential mode 1KV
Operating Temperature	0~40°C
Storage Temperature	-40 °C to 70 °C
Operation Humidity	10%~90%,non condensing
Storage Humidity	5%~95%,non condensing
PWR Green LED	On: Powered on Off: Powered off
1-5 Green LED	On:10/100M Link normal Off: Link blocked Flashing: Data transmitting

# Product Structure Diagram

