

# 8-Port 100Mbps Ethernet Switch (Plastic Shell)



## Product Highlights

- 8\*100Mbps RJ45 ports
- Compliant with IEEE802.3 and IEEE802.3u,IEEE802.3az,IEEE802.3ab standards
- RJ45 port supports 10/100Mbps adaptive
- Supports automatic port flipping (Auto MDI/MDIX)
- The panel indicator LED will monitor the working status and assist in fault analysis
- Flow control method, IEEE802.3x standard for full duplex and Backpressure standard for half duplex

## Hardware Features

Description	Specification
Model	HR-SW0080+
Interface	8 *100Mbps RJ45 ports
Port Standard	IEEE802.3 (Ethernet) IEEE802.3u (Fast Ethernet) IEEE802.3x (Flow Control)
Switching Capacity	1.6Gbps
Packet Forwarding Rate	1.19Mpps
Packet Buffer	768Kbit
MAC Address Table	2K
Transmission Method	Store and Forward
Power Supply	AC 100-240V , 50/60Hz DC 5V 1A
Mainboard Power Consumption	1.12W
Structure Information	Product Dimensions :145*60*21.5mm Packaging Dimensions :146*88*50mm Product Net Weight: 0.089Kg Product Gross Weight:0.167Kg
Packing Information	Carton Dimensions :530*475*315mm Packing Quantity: 100PCS Packing Weight: 17.7KG
Package Contents	Switch 1pcs,Power adapter 1pcs,manual 1pcs,certificate of qualification 1pcs
Fan Quantity	0
Installation	Desktop
Surge Protection	Common mode 2KV, differential mode 1KV
Operating Temperature	0~40°C
Storage Temperature	-40 °C to 70 °C
Operation Humidity	10%~90%, non condensing
Storage Humidity	5%~95%, non condensing
PWR LED	Green LED On: Powered on Green LED Off: Powered off
1-8 LED	Green LED On: Link normal Green LED Off: Link blocked Flashing: Data transmitting

# Product Structure Diagram

