

# 8-Port 10G SFP+ Web Managed Switch



## Product Highlights

- Supports 8\*10G SFP+ ports
- Supports IEEE802.3, IEEE802.3z, IEEE802.3x, IEEE802.3az, IEEE802.3ae, IEEE802.3bz
- SFP+ port supports 10G/1G
- Supports automatic port flipping (Auto MDI/MDIX)
- Adopting a storage and forwarding exchange mechanism
- All ports support line speed switching
- The panel indicator LEDs will monitor the working status and assist in fault analysis
- Support QoS data priority
- Support web management

## Hardware Features

Description	Specification
Model	HR-SWTGW2C8F
Interface	8*10G SFP+ ports
Port Standard	IEEE 802.3: Ethernet Media Access Control (MAC) Protocol IEEE 802.3z: 1000BASE-X Gigabit Ethernet (Fiber optic) IEEE 802.3x: Flow Control IEEE 802.3az (Efficient and Energy saving Ethernet) IEEE 802.3ae (10G Ethernet) IEEE802.3 bz (2.5G Ethernet standard)
Bandwidth	160Gbps
Packet Forwarding Rate	119.04Mpps
Packet Buffer	12Mbit
MAC Address Table	16K
VLAN	VLAN range 1-4094, maximum active VLAN is 4K
Jumbo Frame	10K
Transmission Method	Store and Forward
Surge Protection	Electrostatic ESD: Air 8KV, Contact 6KV (Class B)
Operating Temperature	0~40°C
Storage Temperature	-40 °C to 70 °C
Operation Humidity	10%~90%, non condensing
Storage Humidity	5%~95%, non condensing
Power Supply	AC 100-240V 50/60Hz DC 12V 2A
Mainboard Power Consumption	13.8W
Structure Information	Product Dimensions :220*126*28mm Packaging Dimensions : 259*228*60mm Product Net Weight: 0.62KG Product Gross Weight: 0.86KG
Packing Information	Carton Dimensions : 535*320*480mm Packing Quantity: 20PCS Packing Weight: 18.2KG

Description	Specification
Package Contents	Switch 1pcs, ac adapter 1pcs, manual 1pcs,certificate of qualification 1pcs
Fan Quantity	0
Installation	Desktop
Certification	CE,RoHS,FCC
PWR Green LED	On: Powered on Off: Powered off
SYS Green LED	On: The system is normal Flashing: System startup in progress
10G Link Blue LED	On: Link normal Off: Link blocked Flashing: Data transmitting
2.5G/1G Link Green LED	On: Link normal Off: Link blocked Flashing: Data transmitting
Reset	Long press for 6 seconds to restore factory settings

## Software Features

Description	Specification
L2 Function	
Port	Port Switch configuration
	Port Description configuration
	Port Speed configuration
	Port Duplex configuration
	Port Flow Control configuration
	Jumbo Frame
Link Aggregation	Supports load balance policy; Base on MAC and IP-MAC
	Static and Dynamic Group
	LACP
Storm Control	Up to 8 groups
	Boardcast suppression
	Unknown Multicast
Port Mirroring	Unknown Unicast
	One to one monitor
	Many to one monitor
	Ingress/Egress/Both
Port Security	Up to 4 session groups
	MAC Address Constraints
Port Isolation	Protect/Restrict/Shutdown
	Support
Port Rate-limit	Support
VLAN	Access/Trunk/Hybrid
	VLAN Tunnel (Q-in-Q Tunnel)
MAC Address	VLAN range 1-4094, maximum active VLAN is 4K
	Filtering MAC Address
LLDP	Static MAC address
	LLDP
	LLDP MED

## Software Features

Description	Specification
MAC Address	Filtering MAC Address Static MAC address
Spanning Tree Protocol	STP/RSTP BPDU Filter BPDU Guard Edge Port
Multicast	IGMP Snooping Router Port Static IGMP Join IGMP V1/V2
QoS	Traffic classification, Supporting SP and WRR scheduling Port Priority 802.1P Priority IP DSCP Priority Priority Remarking Supports up to 8 queues per port
ERPS	Main Ring
Services	
Access Protocol	HTTP Session Timeout
Security	DHCP Snooping
Diagnostics	
Ping	Support
Equipment Management	
Manager Access	HTTP SNMP
Manager IP	Static Address Manager VLAN DNS DHCP Client
SNMP	V1/V2C Community Trap Host
SNMP MIB	RFC 1213 MIB-II RFC 1643 Ethernet MIB RFC 2863 Interface MIB
User Management	Support

## Software Features

Description	Specification
SNMP	V1/V2C Community Trap Host
SNMP MIB	RFC 1213 MIB-II RFC 1643 Ethernet MIB RFC 2863 Interface MIB
User Management	Support
Firmware Management	Firmware upgrade
Configuration Management	Upload/Backup Configuration
Save	Support
Restart	Support
Factory Defaults	Support
Standard Compliance	
IEEE 802.3x flow control and back pressure	
IEEE 802.3ad port trunk with LACP	
IEEE 802.1D Spanning Tree Protocol	
IEEE 802.1w Rapid Spanning Tree Protocol	
IEEE 802.1p Class of Service	
IEEE 802.1Q VLAN tagging	
RFC 768 UDP	
RFC 793 TFTP	
RFC 791 IP	
RFC 792 ICMP	
RFC 2068 HTTP	
RFC 1112 IGMP v1	
RFC 2236 IGMP v2	
RFC 3376 IGMP v3	

## Product Structure Diagram

